

STELVIO 66

INGROUND / INCASSI A TERRA

TECHNICAL DATA / DATI TECNICI



IP67



5W / 9W / 9W RGBW /
12W DW



> 90



2200K / 2450K / 2700K / 3000K / 4000K /
RGBW / DW



10° / 30° / 50° / 10°x45° / *Satin Satinato* /
35° RGBW / 20° DW / 40° DW




FINISHES / FINITURE



.T

Trimless
(tempered extra-clear glass)
(vetro temprato extra-chiaro)

TECHNICAL DRAWING / DISEGNO TECNICO




measure unit / unità di misura: mm

PRODUCT CODE / CODICE PRODOTTO

S66 = STELVIO 66

Select one component from each column to specify a complete configuration:
 Seleziona un componente per ogni colonna per la configurazione completa:

	LED colour / Colore LED	Optics / Ottiche	Finish / Finiture	Power / Potenza
	22 = 2200K 25 = 2450K 27 = 2700K 30 = 3000K 40 = 4000K FC = RGBW DW = Dim to Warm	N = 10° M = 30° (20° DW) (35° RGBW) W = 50° (40° DW) E = 10°x45° S = Satin / <i>Satinato</i>	T = Trimless	05 = 5W 09 = 9W CC = 4x700mA RGBW 350mA-14mA DW

Standard configuration example:
 Esempio di configurazione standard:

S66.30.N.T.09 | Stelvio 66 3000K 10° optics trimless 9W

