

TRACER 60

WALL SURFACE / APPLIQUE

TECHNICAL DATA / DATI TECNICI



IP66



10W / 18W



> 90



2700K / 3000K / 4000K



10° / 30° / 50° / 10°x45°



FINISHES / FINITURE



.01

White RAL 9003
Bianco RAL 9003



.02

Black RAL 9005
Nero RAL 9005



.10



Aged solid brass
Ottone anticato



.21

Pre-aged solid brass
Ottone pre-anticato

TECHNICAL DRAWING / DISEGNO TECNICO




measure unit / unità di misura: mm

PRODUCT CODE / CODICE PRODOTTO

T60 = TRACER 60

Select one component from each column to specify a complete configuration:
 Seleziona un componente per ogni colonna per la configurazione completa:

	LED colour / Colore LED	Optics / Ottiche	Finish / Finiture	Power / Potenza
	27 = 2700K 30 = 3000K 40 = 4000K	NN = 10°+10° NE = 10°+10°x45° NM = 10°+30° NW = 10°+50° MM = 30°+30° MW = 30°+50° ME = 30°+10°x45° WW = 50°+50° WE = 50°+10°x45° EE = 10°x45°+ 10°x45°	01 = White RAL 9003 / Bianco RAL 9003 02 = Black RAL 9005 / Nero RAL 9005 10 = Aged solid brass / Ottone anticato 21 = Pre-aged solid brass / Ottone pre-anticato	10 = 10W 18 = 18W

Standard configuration example:
 Esempio di configurazione standard:

T60.30.NN.10.18 | Tracer 60 3000K 10°+ 10° optics aged solid brass / *ottone anticato* 18W





