

TRACER 60

WALL SURFACE / APPLIQUE

TECHNICAL DATA / DATI TECNICI



IP66



10W / 18W



> 90



2200K / 2450K / 2700K / 3000K / 4000K



10° / 30° / 50° / 10°x45°




FINISHES / FINITURE



.01

White RAL 9003
Bianco RAL 9003



.02

Black RAL 9005
Nero RAL 9005



.10



Aged solid brass
Ottone anticato



.21

Pre-aged solid brass
Ottone pre-anticato

TECHNICAL DRAWING / DISEGNO TECNICO



measure unit / unità di misura: mm

PRODUCT CODE / CODICE PRODOTTO

T60 = TRACER 60

Select one component from each column to specify a complete configuration:
 Seleziona un componente per ogni colonna per la configurazione completa:

LED colour / Colore LED	Optics / Ottiche	Finish / Finiture	Power / Potenza
22 = 2200K	NN = 10°+10°	01 = White RAL 9003 / Bianco RAL 9003	10 = 10W
25 = 2450K	NE = 10°+10°x45°	02 = Black RAL 9005 / Nero RAL 9005	18 = 18W
27 = 2700K	NM = 10°+30°	10 = Aged solid brass / Ottone anticato	
30 = 3000K	NW = 10°+50°	21 = Pre-aged solid brass / Ottone pre-anticato	
40 = 4000K	MM = 30°+30°		
	MW = 30°+50°		
	ME = 30°+10°x45°		
	WW = 50°+50°		
	WE = 50°+10°x45°		
	EE = 10°x45°+ 10°x45°		

Standard configuration example:
 Esempio di configurazione standard:

T60.30.NN.10.18 | Tracer 60 3000K 10°+ 10° optics aged solid brass / *ottone anticato* 18W





