







# MAXIMA



Recessed hole / Foro incasso



Ø74 mm




## DESCRIPTION

Maxima is a professional fixed downlight LED luminaire, with a deep recessed COB LED light source and features high efficiency reflector technology for excellent glare control and uniformity. Maxima offers a choice of three colour temperatures as standard (2700K, 3000K and 4000k) and delivers 90 CRI for excellent colour rendering. With binning-free LEDs carefully selected from two-step MacAdam's ellipses, colour consistency is assured throughout the unonovesette portfolio. Available with a choice of three beam angles (20°, 32° and 40°).

## DESCRIZIONE

Maxima è un proiettore professionale a Led da incasso, mediante una posizione molto recessa della sorgente luminosa COB LED. Grazie alla tecnologia a riflettore restituisce un eccellente controllo dell'uniformità e dell'abbagliamento. Maxima offre una scelta fra tre temperature di colore come standard (2700K, 3000K e 4000K) tutte con CRI maggiore di 90 per una eccellente resa cromatica. Binning-free e due-step MacAdam's ellipses LED, assicurano consistenza del colore in tutte le versioni previste da unonovesette. Disponibile con tre diverse ottiche (20°, 32° e 40°).

## OPTICS / OTTICHE:







TECHNICAL DATA / SCHEDA PRODOTTO:

<b>Body:</b>	Die-cast aluminium	<b>Corpo:</b>	Pressofusione di alluminio
<b>Finishes:</b>	White RAL 9003 / Black RAL 9005	<b>Finiture:</b>	Bianco RAL 9003 / Nero RAL 9005
<b>Installation:</b>	Fixing springs	<b>Fissaggio:</b>	Molle di fissaggio
<b>Power supply cables:</b>	30 cm PVC + PVC 2x0,5 mm <sup>2</sup>	<b>Cavo di alimentazione:</b>	30 cm PVC + PVC 2x0,5 mm <sup>2</sup>
<b>Power supply:</b>	Constant current 500mA Max / (350mA-14mA Dim to warm)	<b>Alimentazione:</b>	Corrente costante 500mA Max (350mA-14mA Dim to warm)
<b>Power consumption:</b>	12,9 Watt Max	<b>Potenza assorbita:</b>	12,9 Watt Max
<b>CRI:</b>	>90	<b>CRI:</b>	>90
<b>Bin selection:</b>	Binning free 2 step MacAdam's	<b>Selezione bin:</b>	Binning free 2 step MacAdam's
<b>Lumenoutput (source):</b>	1154 lm (3000K) / 1045 lm - 28 lm (DTW)	<b>Flusso luminoso (sorgente):</b>	1154 lm (3000K) / 1045 lm - 28 lm (DTW)
<b>Operating temperature:</b>	-20°C +50°C	<b>Temperatura di funzionamento:</b>	-20°C +50°C
<b>IP rating:</b>	IP20	<b>Grado di protezione:</b>	IP20
<b>Insulation class:</b>	Class III	<b>Classe d'isolamento:</b>	Classe III
<b>Weight:</b>	235 g	<b>Peso:</b>	235 g
<b>Optics:</b>	20° / 32° / 40° / (20° / 40° DTW)	<b>Ottiche:</b>	20° / 32° / 40° / (20° / 40° DTW)
<b>Energy rating:</b>	A++	<b>Energy rating:</b>	A++
<b>LED colour temperature:</b>	2700K / 3000K / 4000K / (3000K - 1800K DTW)	<b>Temperatura colore LED:</b>	2700K / 3000K / 4000K / (3000K - 1800K DTW)
<b>Lifetime LED:</b>	100000 hrs	<b>Vita media LED:</b>	100000 hrs
<b>Photo biological risk:</b>	RG0 / RG1	<b>Rischio fotobiologico:</b>	RG0 / RG1

FINISHES / FINITURE:

	White RAL 9003 Bianco RAL 9003
	Black RAL 9005 Nero RAL 9005

PRODUCT CODE / CODICE PRODOTTO:

MAX = MAXIMA		Select one component from each column to specify a complete configuration/ Selezionare un componente per ogni colonna per la configurazione completa:		
LED colour / Colore LED	Optics / Ottiche	Finish/Finiture		
27 = 2700K 30 = 3000K 40 = 4000K DW = Dim to warm	N = 20° (20° DTW) M = 32° W = 40° (40° DTW)	01 =White RAL 9003 / Bianco RAL 9003 02 =Black RAL 9005 / Nero RAL 9005		

Standard configuration example/  
Esempio di configurazione standard:

**MAX.30.N.01 Maxima 3000K 20° optics white / bianco**



POWER SUPPLIES 500mA CONSTANT CURRENT / ALIMENTATORE CORRENTE COSTANTE 500mA:

On / Off


Code / Codice	Input	I Out	V Out	Watt	IP	#Maxima
PSU.CX.003	110+240V / 50/60 Hz	500mA	47 V	24	IP20	Max 1
PSU.CX.004	110+240V / 50/60 Hz	500mA	43 V	20	IP20	Max 1

Dimmable / Dimmerabile


Code / Codice	Input	I Out	V Out	Watt	IP	#Maxima
PSU.CX.001 1-10V/PUSH	100+240V / 50/60 Hz	500mA	47 V	15	IP20	Max 1
PSU.CX.002 DALI	100+240V / 50/60 Hz	500mA	47 V	15	IP20	Max 1
PSU.CC.022 DTW DALI	220+240V / 47/53 Hz	350mA	40 V	20	IP20	Max 1

PHOTOMETRICS / CURVE FOTOMETRICHE:


20° - 12,9 Watt





32° - 12,9 Watt



40° - 12,9 Watt



ACCESSORIES / ACCESSORI

 <p>Honeycomb louver Schermo alveolare ACC.001</p>	 <p>Micro prismatic diffuser Filtro diffondente microprismatico ACC.002</p>
---	--